

MULTIPPE MS 2



Grease



Multi purpose extreme pressure lithium/calcium grease with molybdenum disulfide.

APPLICATIONS

Multi purpose EP grease
General Lubrication

Recommendation

- **MULTIPPE MS 2** is a true multi purpose grease, formulated for lubrication of various shock loaded or vibrating applications in transport, agriculture and off road equipment, operating in wet, dusty and/or dry conditions.
- **MULTIPPE MS 2** is suitable for boundary lubrication at high pressures and high temperatures. In case of accidental overheating, the presence of molybdenum disulfide will guarantee good lubrication, and avoid any jamming or sticking.
- Always avoid contamination of the grease by dust and/or dirt when applying. Preferably use a pneumatic pump system or cartridges.

SPECIFICATIONS

Meets the requirements of

- ISO 6743-9: L-XBCEB 2
- DIN 51 502: MPF2K-25

ADVANTAGES

Durable film
Miscible
Mechanical stability
Thermal stability
No harmful substances

- **MULTIPPE MS 2** forms a durable lubrication film, resulting in reduction of maintenance and down-time costs.
- Miscible with most other conventional soap greases.
- Excellent mechanical stability avoiding ejection or loss of consistency during operation.
- Excellent adhesion to metal.
- Good thermal stability, leading to high resistance to temperature variations.
- **MULTIPPE MS 2** does not contain lead, or other heavy metals considered harmful to human health and the environment.

TYPICAL CHARACTERISTICS	METHODS	UNITS	MULTIPPE MS 2
Soap/thickener		-	Lithium/ Calcium
NLGI grade	ASTM D 217/DIN 51 818	-	2
Color	Visual	-	Dark Grey
Appearance	Visual	-	Smooth
Operating temperature range		°C	- 25 to 130
Penetration at 25°C	ASTM D 217/DIN51 818	0.1 mm	265 - 295
Four ball weld load	DIN 51 350-4	daN	380 - 400
Anti-rust performance SKF- EMCOR	DIN 51 802/IP220/NFT 60-135/ISO 11007	rating	0 - 0
Dropping point	ASTM D 566/IP 396/DIN ISO 2176	°C	> 185
Kinematic viscosity of the base oil at 40°C	ASTM D 445/DIN 51 562-1/ISO 3104/IP71	mm ² /s (cSt)	150

Above characteristics are mean values given as an information.

BEHTAM CO.
MULTIPPE MS 2

www.btoil.co

1/1

